

MeshCase



At the first site the case calls up very airy feeling. This is achieved by using the mesh parts that are creating the whole side part of the case. The model can be equipped with the LCD display or there is a choice available without the LCD unit. The case is manufactured for screw-less using.

LCD display

Blue underlighted LCD display shows the actual system temperature, exact time and measures and monitors the fan speed. In case of fan failure, the build-in alarm starts beeping.

MeshSide

Depending on model, the case is assembled with mesh side panel. This panel enables the fluent air circulation and prevents system overheating and can be even assembled with two 80 mm fans or with one 80 mm and one 120 mm fan.

Types



Features	PRIMECOOLER MeshCase AS LCD	PRIMECOOLER MeshCase A LCD	PRIMECOOLER MeshCase A	PRIMECOOLER MeshCase A
LCD display Check if chosen model is assembled with LCD display.	✓	✓	✓	—
Lighting Check if chosen model is assembled with mesh side panel.	✓	—	✓	—

Specification

Dimension	490 × 190 × 440 mm
Weight	6 kg
Space for fans	Front - 80 or 92 or 120 mm Back - 80 or 92 or 120 mm Side (only with MeshSide) - 2 × 80 mm or 80 and 120 mm
External bays	4 × 5.25", 1 × 3.5"
Internal bays	6 × 3.5"
Slots	7 × PCI
Suitable for MB	ATX or microATX

Suitable for PSU	ATX
Front panel	Front panel - 2 × USB 2.0, 1 × eSATA Side panel - 2 × USB 2.0, Audio AC97/HD
Color	Black
Shipping dimension	470 × 240 × 535 mm
Shipping weight	7 kg
Shipping volume	0.060348 m ³

MeshCase / Types



MeshCase A LCD



MeshCase AS LCD



MeshCase A



MeshCase AS